

T2265+ / T2265+ MC



Tally

The T2265+ is undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in their respective speed segments. They are not just sprinters, reliable, heavy workload output is guaranteed for the many years following their purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Highlights at a glance:

- Print speeds up to 1200 cps
- Full range of automatic features minimising operator intervention
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Serial RS232, IBM AS400/iSeries Mainframe Ethernet IPDS

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

The products are well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems. The T2265+ printer is the first high speed matrix printers to incorporate Ethernet on-board.

Available Configuration:

- **T2265+** Standard Product
- **T2265+MC** Heavy Duty Version for up to 9-parts

T2265+/T2265 MC

Print Speed (Standard Model)	: 1200 cps (Fastest Mode); 700 cps (HS Draft), 600 cps (DQ), 200 cps (NLQ), 100 (LQ) at 10 cpi
(MC Version)	: 1067 cps (Fastest Mode); 640 cps (HS Draft), 533 cps (DQ), 180 cps (NLQ), 90 (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	610 pages per hour
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million strokes per pin
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Ethernet 10/100 BaseT
Optional Connectivity	RS-232 Serial, Ethernet with SCS or IPDS, Coax/Twinax with SCS or IPDS
Standard Emulations	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP, Genicom ANSI
Optional Emulations	ECAM 9014, MT460D, MT50, IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable LCP
Consumables	Ribbon: 20 million characters
Standard Paper Handling	Push tractor for continuous paper with straight paper path, tear off and park position
Optional Paper Handling	Additional push tractor (front), Automatic cutting device
Number of Copies	Push tractor front: 1 original + 6 copies or 1 original + 8 copies (MC version only)
Paper Type	Continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 - 419 mm; Length: 76 - 559 mm
Physical Weight	19 kg
Physical Size	622 x 432 x 279 mm (W x D x H)
Acoustic	55 dB(A)
Power Voltage	120 V or 230 V (selectable)
Power Consumption	65 Watt Printing
Temperature	+10° to +35° C; 20% to 80% humidity (not condensing)
Workload	48,000 pages per month
MTBF	10,000 hours
Drivers	Windows 2000/XP/Vista/7/8 and Server 2003/2008; SAP
Standard Warranty	One year with Printhead inclusive
Note	For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase.

DASCOM AP Pte. Ltd.

21 Bukit Batok Crescent
 #29-81 WCEGA Tower
 Singapore 658065
 Tel: +65 6760 8833
 Fax: +65 6760 1066
 www.dascom.com.sg

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 