

## 1225



#### Highlights at a glance:

- Compact 24-pin wide carriage printer
- Up to 498 characters per second
- Ideal for front and back office applications
- Auto switching USB and parallel interface
- Long life ribbon

## Tally

The Tally Dascom 1225 is a 24 pin, 136 column serial dot matrix printer with USB and parallel interfaces as standard. The wide carriage printer is perfect for industrial environments and front and back office applications.

With low running costs, high quality output and an easy to use control panel it's ideal for low volume listing reports, invoices and other critical documents, as well as dispatch notes and labels.

In addition to these applications, the 1225 is also well suited for measurement and control systems.

Amongst the lowest priced matrix printers available today the 1225 also offers a long life ribbon which means fewer ribbon changes, less downtime and lower running costs.



# 1225

Print Speed498 cps (Fastest Mode); 375 cps (HS Draft), 250 cps (Draft)Resolutionup to 360 x 360 dpiThroughput (ECMA 132)336 pages per hourCharacter Density10, 12, 15, 17.1, 20 cpiLine Density1, 2, 3, 4, 6, 8 lpiPrinthead Life400 million strokes per pinMemory48 kBStandard ConnectivityUSB 2.0, Parallel (Bi-directional)Standard EmulationsIBM ProPrinter 2390 Plus, Epson LQ (ESC P/2)FontsDraft, Courier, Roman, Sans Serif, Prestige, Script, Orato	urty, 00 cps (EQ) at 10 cpi
Throughput (ECMA 132)  336 pages per hour  Character Density  10, 12, 15, 17.1, 20 cpi  Line Density  1, 2, 3, 4, 6, 8 lpi  Printhead Life  400 million strokes per pin  Memory  48 kB  Standard Connectivity  USB 2.0, Parallel (Bi-directional)  Standard Emulations  IBM ProPrinter 2390 Plus, Epson LQ (ESC P/2)	
Character Density10, 12, 15, 17.1, 20 cpiLine Density1, 2, 3, 4, 6, 8 lpiPrinthead Life400 million strokes per pinMemory48 kBStandard ConnectivityUSB 2.0, Parallel (Bi-directional)Standard EmulationsIBM ProPrinter 2390 Plus, Epson LQ (ESC P/2)	
Line Density 1, 2, 3, 4, 6, 8 lpi  Printhead Life 400 million strokes per pin  Memory 48 kB  Standard Connectivity USB 2.0, Parallel (Bi-directional)  Standard Emulations IBM ProPrinter 2390 Plus, Epson LQ (ESC P/2)	
Printhead Life400 million strokes per pinMemory48 kBStandard ConnectivityUSB 2.0, Parallel (Bi-directional)Standard EmulationsIBM ProPrinter 2390 Plus, Epson LQ (ESC P/2)	
Memory48 kBStandard ConnectivityUSB 2.0, Parallel (Bi-directional)Standard EmulationsIBM ProPrinter 2390 Plus, Epson LQ (ESC P/2)	
Standard ConnectivityUSB 2.0, Parallel (Bi-directional)Standard EmulationsIBM ProPrinter 2390 Plus, Epson LQ (ESC P/2)	
Standard Emulations IBM ProPrinter 2390 Plus, Epson LQ (ESC P/2)	
Proft Courier Peman Cone Carif Proeting Carint Orate	
Fulls Diart, Couner, noman, Sans Sern, Frestige, Script, Oraci	or, Gothic, Souvenir, OCR-A/B,
10 Barcodes	
Consumables Black ribbon: 7 million characters	
Standard Paper Handling Push tractor and single sheet tray	
Number of Copies 1 Original + 4 copies	
Paper Type Continous forms, cut sheet	
Paper Weight 52-100 g/m <sup>2</sup>	
Paper Size Width: 76 - 419 mm	
Physical Weight 8 kg	
<b>Physical Size</b> 587 x 333 x 155 mm (W x D x H)	
<b>Noise Level</b> (ISO 7779) 55 dB(A)	
Power Voltage 120 V and 220 V models available	
<b>Power Consumption</b> 7.6 W Stand-By	
<b>Temperature</b> +5° to +40° C; 10% to 80% humidity (not condensing)	
Print Volume 6,000 pages per month	
<b>MTBF</b> 10,000 hours	
Standard Warranty One year with Printhead inclusive	
Printer Drivers Windows 98/2000/XP/Vista/7/8 and Server 2003/2008	

### DASCOM AP Pte. Ltd.

21 Bukit Batok Crescent # 29-81 WCEGA Tower Singapore 658065 Tel:+65 6760 8833 Fax: +65 6760 1066

www.dascom.com.sg

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS