

2600 Serial Matrix Printer





Highlights at a glance:

- Print speeds up to 680 cps
- 20,000 pages per month workload
- 256 KBytes buffer
- 24 pin print head produces excellent print quality
- Straight through paper path
- Ethernet, parallel and USB interfaces standard
- 10 million characters long life ribbon

The Tally Dascom 2600 is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price — everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 55 dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Configurations:

• 2600 Standard Product



2600 Serial Matrix Printer 80 Column

Print Speed	680 cps (Fastest Mode); 500 (HS Draft), 333 (Draft), 111 cps (LQ) at 10 cpi
i init opecu	With bi-directional logic seeking
Resolution	Up to 360 x 360 dpi
Character Density	10, 12, 15, 17.1, 20 срі
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 mil dots/pin, 24 pin head
Memory	256 KBytes
Standard Connectivity	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)
Optional Connectivity	Serial RS-232
Standard Emulation	IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP, Epson FX
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes
	and large character printing
Consumable	Ribbon: 10 million characters
Standard Paper Handling	One tractor useable as push (front or rear) or pull (top) version, continuous paper
	with straight paper path and park position, cut sheet front insertion, tear or front off
Optional Paper Handling	Additional push tractor (rear)
Number of Copies	1 original + 6 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 to 278 mm; Length: 76 to 599 mm
Physical Weight	8.6 kg
Physical Size	458 x 265 x 200 mm (W x D x H)
Acoustic	55 dB(A)
Power Voltage	100 - 240 V wide range auto-sensing
Power Consumption	30 Watt Printing; <10 W Sleep Mode
Temperature	+10° to +40° C; 10% to 85% humidity
Workload	20,000 pages per month
MTBF	20,000 power on hours, 25% duty cycle
MVBF	52 Mil lines (except printhead)
Drivers	Windows 2000/XP/Vista/7/8/8.1/10 and Server 2003/2008/2012 R2; SAP; Mac OS
Standard Warranty	One year with printhead inclusive

DASCOM AP Pte. Ltd.

21 Bukit Batok Crescent #29-81 WCEGA Tower Singapore 658065 Tel: +65 6760 8833

Fax: +65 6760 1066 www.dascom.com.sg SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS